

Setback Distances in feet
Benton County, Minnesota Table date: March 8, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
1011A	140	250	350	400
1013A	50	70	80	90
1020A	50	70	80	90
1023A	50	70	80	90
1025A	70	100	130	150
C10B	60	70	80	80
C125A	140	250	340	400
C126B	50	80	110	130
C128A	50	80	100	120
C129A	50	70	100	120
C14A	50	70	80	90
C23B	150	280	380	400
C28A	50	70	80	90
C2A	50	60	70	70
C36A	100	100	100	100
C38B	50	60	90	110
C48a	50	60	60	60
C49A	150	280	380	400
C54B	130	230	310	380
C55A	70	70	70	70
C56A	50	60	60	60
C57A	120	230	310	400
C58A	140	250	340	400
C59A	140	240	320	400
C5C	70	70	70	70
C63B	130	140	150	160
C64A	50	50	50	50
C65A	50	50	50	50
C66A	140	240	320	390
C68B	70	70	70	70
C69B	50	60	70	70
C70B	140	240	320	390
C71A	80	100	100	100
C72B	60	70	80	80
C73A	50	50	50	50

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
Benton County, Minnesota Table date: March 8, 2012

C74A	50	50	50	50
C75A	50	70	80	90
C77A	140	260	350	400
C77B	150	260	350	400
C78A	130	240	320	400
C79A	50	50	50	50
C80A	50	50	50	50
C82A	50	60	60	60
C83A	50	50	50	50
C84A	60	70	70	70
C89A	50	70	80	90
C8A	60	70	80	80
C90A	60	70	70	70
C91B	50	60	70	70
D14B	110	250	350	400
D14B	110	250	350	400
D17A	140	240	320	400
D17A	140	240	320	400
D1B	160	250	320	390
D1B	160	250	320	390
D20A	110	210	290	360
D20A	110	210	290	360
D21A	110	210	290	360
D21A	110	210	290	360
D22A	130	250	350	400
D22A	130	250	350	400
D2A	110	250	350	400
D30A	50	70	80	90
D32A	130	230	310	390
D32A	130	230	310	390
D36B	110	180	240	300
D36B	110	180	240	300
D38A	140	250	350	400
D39A	70	120	160	190
D39A	70	120	160	190
D3A	140	270	370	400
D44A	130	220	300	360
D46A	140	230	310	380

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
 Benton County, Minnesota Table date: March 8, 2012

D47A	160	260	340	400
D47B	170	260	340	400
D48A	130	240	330	400
D50A	130	220	300	360
D51A	150	250	330	400
D51B	160	250	330	400
D52A	140	240	310	380
D55B	120	200	280	340
D56A	90	150	180	210
D61A	130	230	310	390
D64A	130	190	250	310
D64B	130	190	250	310
D6A	130	230	310	380
D7A	130	250	350	400
D7B	130	250	350	400
D9B	180	280	370	400

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.