

Setback Distances
 Jackson County, Minnesota Table date: March 8, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
35	70	100	120	140
86	50	60	80	90
96	50	60	80	90
113	50	60	80	90
114	50	60	80	90
118	50	60	80	100
130	60	80	100	120
197	60	90	110	130
211	50	60	80	100
229	50	60	80	100
255	130	220	310	370
313	50	50	70	80
336	50	50	70	80
362	50	50	80	100
392	120	260	360	400
539	50	70	90	110
664	50	60	70	90
813	60	90	110	130
956	50	60	80	90
1051	50	60	80	90
1833	50	50	60	80
1834	50	60	70	90
1907	60	90	110	140
1914	50	60	70	90
101B	50	80	100	120
102B	50	70	90	110
102B2	50	70	90	110
27B	70	140	190	240
327B	140	220	290	350
39A	150	290	390	400
39B	170	320	400	400
41A	150	250	330	400
41B	150	250	330	400
94B	50	60	80	90
L107A	50	70	90	100

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances
Jackson County, Minnesota Table date: March 8, 2012

L13A	60	90	120	140
L84A	50	60	70	90
L85A	50	60	80	100

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.