

Setback Distances in feet
Lyon County, Minnesota Table date: March 8, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
51	60	80	100	120
86	50	70	90	100
114	50	60	80	90
127	110	190	260	320
184	50	70	90	110
210	50	70	80	100
212	50	60	80	90
219	50	60	70	80
241	50	70	90	100
246	90	190	270	350
276	50	70	90	110
335	60	90	110	140
339	160	290	390	400
341	180	300	400	400
347	130	240	330	400
423	50	60	80	100
446	50	70	90	110
450	90	120	150	180
986	60	90	120	140
1809	50	70	90	110
1810	50	70	90	110
1814	50	60	70	90
1024A	50	50	60	70
127B	110	190	260	320
149B	50	50	60	70
149B2	50	50	60	70
339B	170	280	380	400
341B	180	300	400	400
421B	50	70	80	100
421B2	50	70	90	100
904B2	190	280	380	400
954C2	50	60	80	100
J101B	50	60	80	100
J104A	50	60	80	90
J105A	170	290	400	400

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
Lyon County, Minnesota Table date: March 8, 2012

J106B	50	70	80	100
J107A	50	60	80	90
J11A	50	60	70	90
J12A	160	300	400	400
J17A	50	70	90	100
J18A	90	150	200	240
J195B	50	60	80	90
J199A	50	60	80	90
J1A	50	50	70	80
J232B	50	70	80	100
J236A	50	60	80	90
J237A	50	50	60	80
J237B	50	50	60	80
J23A	50	80	100	120
J240B	50	50	60	70
J243A	50	50	60	70
J251A	50	50	60	70
J25A	50	80	110	130
J26B	50	70	90	100
J2A	50	80	100	120
J31B	170	290	400	400
J32A	50	70	80	100
J48A	50	60	80	100
J57A	50	60	80	100
J75A	140	250	340	400
J75B	140	250	340	400
J77A	50	80	100	120
J7A	100	180	240	300
J7B	100	180	240	300
J80A	50	80	100	120
L139A	170	310	400	400
L142A	50	50	60	80
L173A	50	50	70	80
L198A	50	50	60	70
L198B	50	50	60	70
L201A	50	70	90	110
L202A	50	50	70	80
L214A	60	80	110	130

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
 Lyon County, Minnesota Table date: March 8, 2012

L220A	60	80	110	130
L221A	50	60	70	90
L225B	50	50	70	80
L229A	50	60	80	90
L234A	50	60	80	90
L242B	50	70	80	100
L243A	50	50	60	70
L248B	50	50	70	80
L249A	50	70	80	100
L251A	70	100	120	140
L84A	50	60	70	90
L96B	130	210	280	350

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.