

Setback Distances in feet  
 Otter Tail County, Minnesota      Table date: February 3, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
26	50	50	60	70
34	60	80	100	120
46	100	160	210	260
58	60	90	110	130
59	150	210	230	250
63	130	180	200	220
65	160	210	230	250
107	50	70	90	100
108	50	70	90	110
121	60	80	110	130
180	50	60	80	90
184	50	70	90	110
187	60	110	140	160
191	160	250	340	400
202	130	210	290	350
260	130	220	290	360
290	100	160	220	270
339	160	270	370	400
371	100	170	230	280
418	70	110	140	170
426	150	210	230	250
481	130	240	260	280
494	50	70	90	100
497	70	100	130	150
508	90	160	210	260
540	50	70	80	90
541	200	250	300	350
544	50	70	90	110
624	80	130	180	220
670	60	90	110	120
680	60	80	100	120
698	50	50	60	70
701	60	90	120	150
710	70	120	160	190
715	120	230	310	390

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet  
 Otter Tail County, Minnesota      Table date: February 3, 2012

726	130	240	260	280
746	50	70	80	90
1077	160	260	350	400
1103	170	260	310	360
1110	120	210	270	340
1111	50	110	200	290
1113	50	70	80	90
1114	140	220	280	350
1120	150	230	300	370
1129	50	80	100	120
1136	50	110	200	290
1149	50	70	90	110
1200	60	90	110	140
1214	50	70	90	100
1215	110	200	280	340
1227	70	100	120	140
1230	80	120	150	180
1237	50	60	70	80
1239	60	80	100	110
1240	50	70	90	110
1259	50	70	90	110
1276	60	90	110	120
1289	60	90	110	120
1290	60	90	120	140
1291	70	110	140	160
1293	60	90	120	140
1307	140	220	290	350
1317	50	70	90	100
1321	130	250	300	350
1322	130	200	220	240
1338	90	210	300	380
1339	80	120	150	190
1340	110	190	250	320
1341	170	260	310	360
1342	110	200	280	340
1345	120	230	310	390
1346	50	110	200	290
1348	60	90	110	120

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet  
 Otter Tail County, Minnesota      Table date: February 3, 2012

1349	60	90	120	150
1350	70	110	150	180
1351	50	60	80	90
1365	120	190	250	320
1396	90	140	190	230
1397	150	190	220	250
1874	160	270	360	400
1943	130	210	270	330
1975	190	320	400	400
1102B	80	110	140	160
1104B	50	70	90	100
1105B	70	120	150	180
1131B	160	280	380	400
1195A	110	200	270	330
1195B	110	200	270	330
1196B	100	190	260	330
1208B	50	70	100	110
1212B	50	60	80	100
1216B	60	90	110	140
1232B	80	110	130	160
1234B	50	50	60	70
1275B	60	100	130	160
127A	120	200	270	340
127B	120	200	270	340
1304A	80	130	170	210
1319B	160	270	360	400
1320B	140	250	330	370
1324B	60	90	120	140
1344B	120	230	310	380
1347B	60	110	160	190
168B	50	70	90	100
1825B	50	70	80	90
258A	150	250	340	400
258B	150	250	340	400
267B	60	90	120	140
293B	70	100	120	130
341A	170	290	380	400
341B	170	290	380	400

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet  
 Otter Tail County, Minnesota      Table date: February 3, 2012

38B	50	70	90	100
402C	180	290	380	400
406A	150	250	340	400
406B	150	250	340	400
422B	50	70	90	110
441A	170	280	380	400
441B	170	280	380	400
53B	60	110	140	170
567A	160	280	380	400
567B	160	280	380	400
609B	150	190	210	230
705B	130	240	320	340
707B	80	130	180	220
711B	170	290	380	400
716B	140	170	190	220
769B	50	70	90	100
776B	70	90	120	140
778B	150	250	340	400
779B	50	60	70	80
7A	120	210	280	350
7B	120	210	280	350
7C	120	210	280	350
902B	50	60	80	90
957B2	100	160	210	270

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.