

Setback Distances in feet
 Renville County, Minnesota Table date: March 8, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
35	70	110	140	160
85	60	80	110	130
86	50	60	80	90
112	50	50	60	70
113	50	60	70	90
118	50	70	80	100
130	50	60	80	100
134	50	60	80	90
156	140	250	350	400
227	120	210	290	360
247	120	220	290	310
255	120	200	300	360
282	140	250	340	400
318	100	150	260	320
336	50	60	80	100
386	50	60	80	90
392	120	220	330	400
423	50	70	80	100
446	50	70	90	110
519	60	90	110	130
574	50	60	70	90
575	50	60	70	90
610	60	80	110	130
817	50	60	80	90
899	50	50	60	70
927	50	50	60	70
956	50	60	70	90
978	50	60	70	80
1080	50	60	80	90
1100	50	70	90	100
1101	50	60	80	90
1205	50	80	90	110
1262	50	70	90	110
1268	70	110	130	160
1269	80	110	130	150

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
Renville County, Minnesota Table date: March 8, 2012

1285	60	80	100	120
1286	60	80	100	120
1287	60	80	110	130
1374	50	50	70	80
1382	60	80	100	120
1389	50	80	90	110
1390	50	80	90	110
1802	50	70	90	110
1833	50	50	60	80
1834	50	50	60	80
1900	50	60	70	90
1917	50	60	80	90
1958	60	110	150	180
1999	70	100	130	160
102B	50	70	90	110
1355B	50	70	90	110
1369A	60	80	100	120
1369B	60	80	100	120
1370B	50	70	90	100
1371B	60	80	100	120
1386B	50	70	90	100
1388B	50	60	80	90
1392B	80	140	180	220
1845A	190	310	400	400
1845B	200	310	400	400
27A	100	160	210	260
27B	100	160	210	260
327A	130	220	290	360
327B	130	220	290	360
39A	150	290	390	400
39B	150	290	390	400
463A	90	150	200	250
463B	90	150	200	250
887B	50	70	90	110
920B	50	70	90	110
L107A	50	70	90	100
L13A	60	90	120	140
L163A	50	60	80	100

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
 Renville County, Minnesota Table date: March 8, 2012

L164A	50	70	80	100
L179A	50	50	50	60
L184A	50	50	50	60
L185B	50	50	50	50
L187A	60	90	100	120
L192A	50	70	80	90
L200A	50	80	90	100
L201A	50	70	90	110
L206B	50	50	50	50
L33A	50	50	50	60
L33B	50	50	50	60
L34A	50	50	50	60
L83A	50	60	80	90
L85A	50	60	80	100

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.