

Setback Distances in feet
 Sibley County, Minnesota Table date: March 8, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
35	80	120	160	190
86	50	60	80	90
109	50	50	70	80
110	50	60	80	90
112	50	50	60	70
113	50	60	70	90
114	50	60	80	90
118	50	70	80	100
130	50	60	80	90
134	50	60	80	100
239	50	50	70	80
317	50	80	100	120
329	60	80	110	130
336	50	50	70	80
386	50	70	90	110
525	50	70	140	170
539	50	70	90	120
743	50	70	90	110
919	50	60	70	90
946	50	70	90	110
956	50	60	70	90
978	50	50	60	80
1016	50	60	70	90
1075	50	60	70	90
1081	70	100	130	160
1093	50	60	70	90
1833	50	70	80	100
1834	50	50	70	80
1999	70	100	130	160
102B	50	70	90	110
106B	50	60	80	90
1901B	50	60	80	90
222B	110	170	220	270
27B	100	160	210	260
463B	100	160	210	260

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
 Sibley County, Minnesota Table date: March 8, 2012

5B	150	290	390	400
887B	50	70	90	110
920B	50	70	90	110
944B	50	60	80	90
94B	50	80	100	110
L107A	50	70	90	100
L13A	60	90	120	140
L163A	50	60	80	100
L83A	50	60	80	90
L84A	50	60	70	90
L85A	50	60	80	100

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.