

Setback Distances in feet
 St. Louis County, Minnesota Table date: March 7, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
1020A	50	70	80	90
1026A	70	100	130	150
1034A	70	100	130	150
A1B	130	210	280	340
A1B	130	210	280	340
A21B	90	180	260	320
A28A	200	250	300	350
A29A	200	250	300	350
A3B	130	230	310	380
A42B	80	130	170	200
A45B	60	80	100	120
A4A	120	210	280	340
A5A	130	230	310	380
B100A	200	250	300	350
B104A	50	60	80	90
B107A	50	70	80	90
B108A	50	70	80	90
B10B	220	360	400	400
B118A	200	250	300	350
B119A	50	70	80	90
B11B	50	70	90	110
B11B	50	70	90	110
B120A	200	250	300	350
B123A	50	70	80	100
B124A	50	60	70	80
B125B	50	60	70	90
B127B	50	60	70	90
B129B	50	60	70	90
B129B	50	60	70	90
B135A	60	90	110	130
B13B	130	210	280	340
B13B	130	210	280	340
B144A	50	60	80	90
B145B	50	60	70	80
B147A	200	250	300	350

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
 St. Louis County, Minnesota Table date: March 7, 2012

B148A	200	250	300	350
B14A	200	250	300	350
B151A	50	80	100	120
B152A	200	250	300	350
B15A	50	70	100	110
B16B	90	200	280	350
B17B	90	180	260	320
B18A	50	60	80	90
B19B	50	60	80	100
B1C	50	70	90	110
B212A	50	60	80	90
B213A	50	60	70	90
B220A	60	90	120	140
B221A	70	100	130	150
B234A	60	90	120	140
B235A	100	170	220	270
B236A	100	170	220	270
B237A	90	140	190	230
B238A	90	160	210	260
B239B	100	160	220	260
B23A	50	60	80	90
B240D	90	140	190	220
B24B	50	60	80	90
B255A	50	70	80	90
B256A	50	70	80	90
B266A	100	180	250	310
B268D	70	100	130	150
B268E	70	100	130	150
B269A	60	100	130	160
B270A	60	90	110	140
B271A	60	90	110	140
B274A	200	250	300	350
B275A	200	250	300	350
B276A	50	70	80	90
B277A	200	250	300	350
B279A	100	170	230	290
B2A	50	70	90	100
B30A	100	160	220	270

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
 St. Louis County, Minnesota Table date: March 7, 2012

B36B	120	230	310	380
B37B	90	200	280	350
B39A	120	210	280	340
B41B	130	220	310	380
B4A	50	70	90	100
B54A	60	90	120	150
B55A	50	80	100	120
B56A	60	90	120	150
B57B	60	100	140	170
B58B	130	230	310	380
B61A	50	70	80	90
B67A	200	250	300	350
B68A	130	230	310	380
B72A	120	230	320	390
B73A	60	90	120	150
B74A	90	140	190	240
B79B	120	220	300	370
B80A	200	250	300	350
B81A	50	70	80	90
B82A	200	250	300	350
B83A	200	250	300	350
B84B	50	70	90	110
B85A	200	250	300	350
B86A	60	90	110	130
B99A	50	70	80	90
B9A	50	60	80	90
E12A	60	90	120	150
E12A	70	90	120	140
E13E	60	90	120	150
E15A	50	50	70	80
E15B	50	50	60	80
E1A	50	80	100	110
E5A	60	90	110	130
F116A	200	250	300	350
F117A	220	370	400	400
F117B	220	370	400	400
F118B	130	270	370	400
F120A	150	250	340	400

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
 St. Louis County, Minnesota Table date: March 7, 2012

F120B	150	250	340	400
F121A	130	270	370	400
F121B	130	270	370	400
F122B	130	270	370	400
F123B	150	250	340	400
F124B	220	370	400	400
F125A	140	270	380	400
F126A	170	300	400	400
F127A	90	220	310	400
F128A	110	250	360	400
F129A	50	70	80	90
F149D	130	270	370	400
F152A	70	100	130	150
F153B	70	100	130	160
F157C	150	250	340	400
F161A	200	250	300	350
F162A	220	360	400	400
F164B	190	360	400	400
F166A	60	100	130	160
F168A	50	60	80	90
F169B	50	60	80	100
F16B	140	240	330	400
F170A	200	250	300	350
F171D	130	220	310	380
F172B	90	200	280	350
F174B	100	140	170	200
F175A	200	250	300	350
F176A	80	140	200	240
F17A	60	100	130	160
F180A	120	200	270	330
F181A	110	190	260	320
F182B	110	200	270	330
F183B	110	200	270	330
F184B	100	160	230	290
F185B	130	240	330	400
F186C	130	330	400	400
F188A	70	110	140	170
F189B	50	60	80	90

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
 St. Louis County, Minnesota Table date: March 7, 2012

F190B	50	60	80	90
F191A	60	100	140	170
F192B	60	100	130	160
F193A	50	60	80	90
F196A	60	90	120	150
F19A	150	300	400	400
F201B	220	360	400	400
F20A	60	90	120	140
F213B	50	60	80	100
F214A	60	100	130	160
F215A	200	250	300	350
F216A	200	250	300	350
F23B	220	360	400	400
F24A	140	260	360	400
F26C	140	270	370	400
F27C	190	360	400	400
F28B	220	400	400	400
F31B	220	400	400	400
F38B	50	60	80	100
F40B	220	360	400	400
F41B	130	230	310	380
F42A	120	210	280	350
F43A	130	230	310	380
F7B	100	160	230	290
F9A	130	230	320	390
F9B	130	230	320	390

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.