

Setback Distances in feet
 Swift County, Minnesota Table date: March 8, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
J10A	50	60	80	90
J10B	50	60	80	90
J11A	50	60	70	90
J12A	160	300	400	400
J13A	50	70	90	110
J15B	80	130	170	210
J16A	50	70	90	110
J17A	50	70	90	100
J18A	90	150	200	240
J19A	130	200	270	330
J1A	50	50	70	80
J20A	100	170	230	280
J21A	110	170	210	250
J22A	140	220	290	360
J23A	50	80	100	120
J25A	50	80	110	130
J26B	50	70	90	100
J27A	70	110	150	180
J28A	50	60	80	100
J29A	50	60	80	90
J2A	50	80	100	120
J30A	50	70	100	110
J31B	170	290	400	400
J32A	50	70	80	100
J34B	50	80	100	110
J35B	50	60	80	100
J38B	80	120	160	190
J3A	90	150	210	260
J40A	50	50	70	80
J41A	100	140	170	200
J43A	70	100	120	130
J44B	80	110	140	170
J46B	50	70	90	110
J47A	50	60	80	90
J48A	50	60	80	100

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
 Swift County, Minnesota Table date: March 8, 2012

	50	60	80	90
J49A	50	60	80	90
J50A	50	60	80	100
J51A	50	70	90	110
J52A	60	100	120	150
J53A	50	80	110	130
J54A	170	310	400	400
J55A	70	110	140	170
J56A	50	60	80	90
J57A	50	60	80	100
J58B	100	170	240	290
J59A	90	200	330	400
J5A	150	250	340	400
J60B	50	60	70	90
J60C	50	60	70	90
J61A	50	70	90	110
J62C	50	70	90	100
J63A	50	80	110	130
J64A	50	80	100	110
J65A	90	200	280	350
J66A	60	90	110	140
J67A	100	220	310	390
J68A	50	70	90	110
J6A	100	200	290	360
J7A	100	180	240	300
J7B	100	180	240	300
J8A	90	140	190	230
J8B	90	150	190	230
J9A	140	280	390	400
L164A	50	70	80	100
L33A	50	50	50	60
L33B	50	50	50	50
L34A	50	50	50	50

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.