

Setback Distances in feet
Wabasha County, Minnesota Table date: March 6, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
Az	80	120	150	180
BbA	170	300	400	400
BbB	180	310	400	400
BkA	130	200	260	320
BkB	130	200	260	320
BrA	150	250	340	400
BrB	160	270	360	400
BtA	130	200	270	330
BtB	130	210	270	330
BtC2	130	210	270	330
CaB	50	70	90	110
ChA	60	90	120	140
ChB	60	90	120	140
Co	50	80	100	130
DhA	70	100	120	150
DmA	70	100	120	150
DmB	70	100	120	150
FaA	60	80	110	130
FbA	50	70	90	110
FbB	50	70	90	110
FbC2	50	70	90	110
Gm	60	80	110	130
Hu	80	110	140	170
MbA	50	50	60	70
MbB	50	50	60	70
MdA	120	250	350	400
MdB	120	250	350	400
MdC2	120	250	350	400
Mn	100	170	230	280
MuA	80	120	150	180
MuB	80	120	150	180
N501B	60	90	110	140
N501C2	60	90	110	140
N514B	60	90	120	140
N518B	80	120	150	170

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
Wabasha County, Minnesota Table date: March 6, 2012

N518C2	80	120	150	170
N519B	80	110	130	140
N520B	80	110	130	150
N521B	70	110	140	170
N521C2	70	110	140	170
N555B	60	90	110	140
N555C2	60	90	110	140
N572C2	60	90	110	140
N574B	60	90	110	140
N574C2	60	90	110	140
N578B	70	110	140	170
N585B	80	120	150	180
N585C2	80	120	150	180
N590B	60	90	120	140
N590C2	60	90	120	140
N606A	60	90	170	230
N614A	110	210	300	370
N619A	70	110	140	160
N644A	160	250	330	400
N645A	70	110	140	170
N646A	70	90	110	130
N647A	60	140	200	250
N648A	130	210	270	330
N649A	50	100	150	190
N660A	100	170	230	280
N665A	60	100	120	140
N670A	60	90	120	140
PaA	150	240	310	380
PaB	150	240	310	380
PaC	150	240	310	380
PbA	70	110	140	160
PoA	70	110	140	160
PoB	70	100	130	160
RaA	50	60	80	90
RaB	50	60	70	80
RaC2	50	60	70	80
ReB	50	70	90	100
ReC2	50	70	90	100

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
Wabasha County, Minnesota Table date: March 6, 2012

RkB	50	70	90	100
RkC2	50	70	90	100
SpA	130	200	260	320
SpB	130	200	260	320
ThA	100	180	250	320
ThB	100	180	250	320
WaA	130	250	370	400
WaB	130	250	370	400
WaC2	130	250	370	400
WvB	120	200	260	330
WvC2	120	200	260	330
Zb	140	220	290	350
ZgA	50	70	90	110
ZgB	50	70	90	110

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.