

Setback Distances in feet
 Wadena County, Minnesota Table date: March 8, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
126	130	210	270	330
187	60	110	140	160
260	130	220	290	370
261	120	210	270	340
540	50	70	80	90
541	200	250	300	350
543	50	110	200	290
544	50	70	90	110
545	50	70	90	110
701	60	90	120	150
793	130	250	300	350
834	170	270	350	400
1941	180	290	380	400
1942	160	260	350	400
1943	130	210	270	330
1956	170	280	310	340
1968	180	300	390	400
1969	200	300	400	400
1975	190	320	400	400
1984	80	130	160	200
1985	60	100	130	150
139B	160	250	320	380
1957B	160	250	320	390
1970B	140	210	280	340
207A	150	240	310	380
207B	150	240	310	380
374B	160	270	360	400
406A	150	250	340	400
406B	150	250	340	400
454B	170	260	330	400
458A	140	210	280	340
458B	140	210	280	340
567A	160	280	380	400
567B	160	280	380	400
720B	140	250	330	370

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
Wadena County, Minnesota Table date: March 8, 2012

82B	150	240	320	390
-----	-----	-----	-----	-----

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.