SCRAPE / SEDIMENT REMOVAL MATERIAL PLACEMENT LOCATION									SCRAPE / SEDIMENT REMOVAL DESIGN TABLE								
CRAPE ID# SC	SCRAPE TYPE	RANDOM FILL	BERM / SLOPE FILL	DITCH FILL	SALVAGE TOPSOIL	ADJACENT UPLANDS	A	APPROXIMATE LENGTH (FEET)	B	APPROXIMATE LENGTH (FEET)	©	APPROXIMATE EXCAVATION DEPTH (FEET)	©	APPROXIMATE SIDE SLOPE (FEET)	ESTIMATED EXCAVATED QUANTITY (C.Y.)		
			L CRIPTION AND/OR SHEET # FOR THE DIMENT REMOVAL. IF THERE ARE NO OTHERWISE DIRECTED BY	CELLS FILLED IN, THEN THE EX				* THE LENGTHS, DEPT	THS, AND	SLOPES PROVIDED ARE	AVERAGES	S. DIMENSIONS MAY VA	RY. (SEE C	ONSTRUCTION REQUIRE	MENTS BELOW).		
VATERIAI	PLACEN	MENT REQUIR				EXISTING	0										

DIRECTED BY ENGINEER.

LOCATION	DESCRIPTION
RANDOM FILL	PLACEMENT OF EXCAVATED SCRAPE / SEDIMENT REMOVAL MATERIAL FOR RANDOM FILL SHALL BE TO DIMENSIONS SHOWN IN DRAWINGS OR OTHERWISE DIRECTED BY ENGINEER.
WAVE BERM / SLOPE FILL	PLACEMENT OF EXCAVATED SCRAPE / SEDIMENT REMOVAL MATERIAL FOR WAVE BERM / SLOPE FILL SHALL BE TO DIMENSIONS SHOWN IN DRAWINGS OR OTHERWISE DIRECTED BY ENGINEER.
DITCH FILL	PLACEMENT OF EXCAVATED SCRAPE / SEDIMENT REMOVAL MATERIAL FOR DITCH FILL SHALL BE TO DIMENSIONS SHOWN IN DRAWINGS OR OTHERWISE DIRECTED BY ENGINEER.
SALVAGE TOPSOIL	TOPSOIL IS TO BE STRIPPED, STOCK PILED, AND THEN PLACED / GRADED BACK INTO THE EXCAVATED SCRAPE AREA. TOPSOIL STRIPPING DEPTHS SHALL BE 4 TO 6 INCHES UNLESS OTHERWISE DIRECTED BY ENGINEER.
ADJACENT UPLANDS	ANY EXCESS EXCAVATED MATERIALS SHALL BE PLACED ON ADJACENT UPLANDS SHALL BE WELL GRADED, AND CONFORM TO EXISTING TOPOGRAPHY, UNLESS OTHERWISE DIRECTED BY ENGINEER.


CONSTRUCTION REQUIREMENTS

WETLAND SCRAPE / SEDIMENT REMOVAL:

- THE PROJECT ENGINEER OR THE ENGINEER'S REPRESENTATIVE MAY CHANGE THE DEPTH, SLOPE, SHAPE, SIZE, OR LOCATION OF THE EXCAVATION AT THEIR DISCRETION.
- THE FINISHED SHAPE OF THE EXCAVATION SHALL BE IRREGULAR AS SHOWN.
- THE FINISHED SURFACE OF THE EXCAVATION SHALL BE ROUGH (NOT GRADED SMOOTH).


FINAL QUANTITIES AND PAYMENT

- EXCAVATION QUANTITIES WILL BE FIELD VERIFIED / MEASURED FOR PAYMENT UPON COMPLETION OF THE EXCAVATION. PLACEMENT REQUIREMENTS (LOCATION) SHALL BE INCIDENTAL TO SCRAPE / SEDIMENT REMOVAL.
- THE VOLUME (C.Y.) SHOWN FOR EACH EXCAVATION IS THE MAXIMUM QUANTITY ALLOWABLE FOR PAYMENT WITHOUT PRIOR APPROVAL FOR AN INCREASE FROM THE
- UNLESS OTHERWISE SPECIFIED THE PLACEMENT OF ALL EXCAVATED MATERIALS SHALL BE INCIDENTAL TO THE COST OF THE EXCAVATION (I.E., NOT A PAY ITEM).




PLANVIEW OF SCRAPE / SEDIMENT REMOVAL

NOT TO SCALE



SECTION OF TYPE A SCRAPE / SEDIMENT REMOVAL

NOT TO SCALE



SECTION OF TYPE B SCRAPE / SEDIMENT REMOVAL

NOT TO SCALE

PROJECT #:

WETLAND RESTORATION PLAN

SHEET NO. OF